



Logo Placements

1539 High-Vis Jacket CL 2

Recommended logo placements

Embroidery and Heat Seal

- 1 Left breast, top of logo 10 cm below top of arrow
- 2 Left sleeve, middle of logo 15 below en of reflective band
- 3 Right breast, in line with placement 1
- 4 Right sleeve, middle of logo 15 below en of reflective band
- 6 Back, top of logo 12 cm below neck sea,
- 63 Back, 5 cm above end of jacket



Maximum size of logo cm² to keep classification EN 20471

| | | |
|------|-----------------|----------|
| Size | cm ² | cm |
| All | 1674 | 40x40 cm |

To maintain the Class 3 certification, see maximum logo size in table to the right.

If you choose a logo bigger than our recommendation, we do not guarantee that the garment meets the EN 20471 Norm.

Embroidery is not possible, there is no zip, so we cannot seal the embroidery and make it water proof.

| Art. | 1539 | |
|----------|-----------|------------|
| Max Size | Heat Seal | Embroidery |
| 1 | 120x120 | 80x80 |
| 2 | 120x120 | 80x80 |
| 3 | 80x120 | NO |
| 4 | 120x120 | 80x80 |
| 6 | 280x270 | 270x200 |
| 63 | 280x100 | 270x100 |

- 1Y Add Y after the placement and it will be turned from bottom to top
- 1B Add B after the placement and it will be below the (1B)
- 1Z Add Z after the placement and it will be turned from top to bottom

